

Seri / Series T-YA - 400

TEKNİK ÖZELLİKLER

- ❑ **Gövde** : Pirinç (Ms 58)
- ❑ **Çekirdek** : Paslanmaz Çelik
- ❑ **Diyafram** : Viton
- ❑ **Kovan** : Paslanmaz Çelik (AISI 316)
- ❑ **Bağlantı** : R Dişli (DIN 2999, ISO R7)
- ❑ **Akışkan Sıcaklığı** : Viton (-10 / +160 °C),
- ❑ **Ortam Sıcaklığı** : (-20 / +40 °C)
- ❑ **Bobin Gücü** : 10 - 14 Watt
- ❑ **Soket Koruma Sınıfı** : IP 65
- ❑ **Bobin Gerilimi** : 12, 24,42, 48, 110, 220 AC/DC
- ❑ **Gerilim Toleransı** : ±%10 V AC/DC
- ❑ **Kullanıldığı Yerler** : Fuel Oil ,Yağ

TECHNICAL FEATURES

- ❑ **Body** : Brass (Ms 58)
- ❑ **Plunger** : Stainless Steel
- ❑ **Sealing** : Viton
- ❑ **Tube** : Stainless Steel (AISI 316)
- ❑ **Threaded** : R Screw (DIN 2999, ISO R7)
- ❑ **Medium Temperature**: Viton (-10 / +160 °C),
- ❑ **Ambient Temperature** : (-20 / +40 °C)
- ❑ **Power** : 10 - 14 Watt
- ❑ **Connector Protection Class** : IP 65
- ❑ **Coil Voltage** : 12, 24, 42, 48, 110, 220 AC/DC
- ❑ **Voltage Tolerance** : ±%10 V AC/DC
- ❑ **Applications** : for Fuel oil, Hydraulic Oil

34

35

36

37

38

Model	Ölçü Size	Orifis Orifice (mm)	Kv (m ³ /h)	Fark Basınç Differential Pressure		Conta Seal	Resim Picture	Açıklama Description
				min. (Bar)	max..(Bar)			
T - YA 400	G 1/8"	2.5	0.29	0	30	RUBY	34	Direkt Çekmeli Direct Operated
T - YA 400.A		3.2		0	30		34	
T - YA 401	G 1/4"	2.5	0.29	0	30		34	
T - YA 401.A		3.2		0	30		34	
T - YA 402	G 3/8"	12.5	2.6	0.5	16	Viton	35	Pilot Kontrollu Diyaframlı Pilot Operated with Diaphragm
T - YA 402.A					16		36	
T - YA 402.1					40		35	
T - YA 402.1A					40		36	
T - YA 403	G 1/2"	14.5	3.5	0.5	16		35	
T - YA 403.A					16		36	
T - YA 403.1					40		35	
T - YA 403.1A					40		36	
T - YA 404	G 3/4"	17	4.2	0.5	16	35		
T - YA 404.A					16	36		
T - YA 404.1					40	35		
T - YA 404.1A					40	36		
T - YA 405	G 1"	17	4.3	0.5	16	37		
T - YA 405.A					16	38		
T - YA 405.1					40	37		
T - YA 405.1A					40	38		
T - YA 409	G 1 1/4"	32	14	0.5	10	22		
T - YA 409A					10	23		
T - YA 406	G 1 1/2"	40	22	0.5	10	22		
T - YA 406A					10	23		
T - YA 407	G 2"	50	40	0.5	10	22		
T - YA 407A					10	23		
T - YA 408.8	G 1/8"-3/2	2.5	0.09	0.5	25	RUBY	34	Direkt Çekmeli Direct Operated
T - YA 408.4	G 1/4"-3/2	2.5					25	

A: Normalde Açık / Normally Open

T: Tepeden Girişli / Input from top